


Comparison of Anti-tracking and Delay Performance of Welded Fiber Pads



Comparison of Anti-tracking and Delay Performance of Welded Fibe




Key characteristics include all dielectric structure, light weight, good electromagnetic resistance, and suitability for installation on high voltage power lines. Detailed specifications are provided for fiber, ...



Compared with the general products, the anti-tracking sheathing material has the advantages that the performance such as the product surface, the density, the melt index, the tensile ...



Note 1: Please contact your sales agent for information about the total packaging dimensions and weight, as well as for higher fiber counts and different drum lengths available



The outer insulating sheath of such a cable is made of polymers that are resistant to electrical discharges that damage the sheath surface. Test methods for evaluating the cable for ...



This paper reports the electrical tracking performance of three commercially available HSATT samples. Crosslinked polyethylene (XLPE) is the key ingredient for heat shrinkable materials.



In this study, we selected an appropriate seam-tracking signal, developed an algorithm to track the welding location based on the selected signal, and evaluated the seam-tracking...



Read all about our track-resistant ADSS Standard cable which can withstand long spans of 115 kV or greater on overhead lines, from our ADSS cable manufacturers.



Anti-track Short Span Aerial Optic Fibre TI-TRACK OPTIC FIBRE is constructed of fibres inside multiple gel filled loose tubes. The cable is strengthened by a glass reinforced plastic strength member (GRP), ...



The invention relates to an anti-tracking polyethylene sheathing material which comprises a mixture of high-density polyethylene resin and low-density polyethylene resin, and an...



Anti-Tracking materials are engineered for maximum safety and reliability in high-voltage applications. These materials prevent the formation of conductive paths, reducing the risk of electrical tracking and ...

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

