

FC connector 2 5 ceramic insert



FC connector 2 5 ceramic insert



They feature a 2.5 mm ferrule and a threaded metal coupling nut, for a secure connection in laboratory testing for consistent results and in high vibration environments.



The FC connector is a fiber optic connector with a screw thread locking mechanism to withstand high-vibration environments Radiall's FC connector is composed of a plated nickel housing and a 2.5 mm ...



The 2.5mm OD Ceramic Ferrule with Flange for SC/FC/ST Fiber Connector is a high-precision zirconia ferrule designed to ensure accurate fiber alignment and superior optical performance.



Thorlabs offers FC/PC connectors with 2.0 mm narrow keys and ceramic ferrules. Our smaller bore connectors (Item #s 30128C3, 30140E1, and 30150C1) accommodate our small-core multimode fibers.



This FC multimode fiber connector is designed for dependable optical terminations in multimode fiber applications. Built with a ceramic ferrule for accurate alignment and stable signal transfer, the FC ...



The FC connector features a 2.5 mm ferrule and a threaded metal coupling nut, for a secure connection in high vibration environments and in laboratory testing for consistent results.



Our male FC PC connectors have 2.5mm pre-polished zirconia ceramic ferrules with a slight spherical end-face. They also feature a screw-on collet that ensures precise connections in high vibration ...



The connector is precision made and manufactured to demanding specifications. The combination of a Ceramic ferrule with precision Nickel plated Brass housing provides consistent long-term mechanical ...



Upgrade your network performance with our professional-grade Fiber Optic Connectors. Featuring high-precision Zirconia Ceramic ferrules for minimal signal loss, our selection includes industry-standard ...



The 2.5mm OD Ceramic Ferrule with Flange for SC/FC/ST Fiber Connector is a high-precision zirconia ferrule designed to ensure accurate fiber ...



Fiber connectors, adapters, dust caps, sleeves, and cleaning consumables (sticks, one-click dry cleaners) for 2.5mm ferrule connectors (SC, ST, FC, SMA).

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

