


## Tlink switch 1 optical fiber 8 electrical components



### Overview

This user manual explains how to use a TLink option module to create a TLink system. A TLink system can use multiple drives and is based on Connected Components Workbench™ (CCW) software and PowerFlex® 750-Series AC Drives with TotalFORCE® Control. This publication contains the following new or. Page 1 TLink Option Module Catalog Numbers 20-750-TLINK-XT, 20-750-TLINK-FOC-5, 20-750-TLINK-FOC-10, 20-750-TLINK-FOC-50 User Manual Original Instructions. Page 2 If this equipment is used in a manner not specified by the manufacturer, the protection provided by the equipment may be impaired. Fiber optic cables in 5, 10, or 50 meter lengths. The TLink option module network consists of one TLink option module that is configured as the leader to transmit data, and, in Mode A, up to.

## TLink switch 1 optical fiber 8 electrical components



A TLink-based system consists of at least two TLink option modules that are installed in two or more drives that are connected by a fiber-optic cable. One drive is considered the leader and all other ...



These hot-swappable, thumb-sized devices plug into the "SFP slots" on your switches or routers. Their job is simple yet critical: they convert the electrical signals from the switch into light signals (for fiber ...



Connect up to 8 devices directly to your router using TP-Link's secure, reliable gigabit network switches that are easy to install and more intelligent than a hub



The TLinkoption module network consists of one TLink option module that is configured as the leader to transmit data, and, in Mode A, up to three modules that are configured as followers to receive data ...



Allen-Bradley 20-750-TLINK-FOC-50 PowerFlex 750 Kit, TLINK Option Module Fiber Optic Cable, 15m



Enhance your automation setup with the Allen-Bradley PowerFlex 750T Kit TLINK Fiber 50m, featuring a robust fiber optic cable for reliable connectivity and efficient performance.



The PowerFlex® TLink option module is used to update parameters in PowerFlex 750-Series Products with TotalFORCE® Control through a fiber-optic interface.



For detailed information on installing the TLink option module and fiber optic cables, see the PowerFlex 20-750-TLINK-XT TLink Option Module Installation Instructions, publication 750COM-IN100.



Appendix A for a complete list of TLink parameters and settings. Set the TLink fault actions in your drives according to your application needs.



PowerFlex 20-750-TLINK-1 TLink Fiber Optic Cables Product Information, Provides basic safety precautions for fiber-optic cables that are used with TLink option publication 750COM-PC100. modules.

## Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://gdroofing.co.za>

Email: [sales@gdroofing.co.za](mailto:sales@gdroofing.co.za)

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

