



Wall-mounted double-door distribution box



Wall-mounted double-door distribution box



Multilink wall mount fiber distribution boxes include solutions for patch cable interconnection or a combination of splicing and patching. We separate these products into multiple groups based on ...



Explore Double Door Electrical Enclosures for spacious and easily accessible protection of larger industrial electrical systems. Durable cabinets with various NEMA and IP ratings.



These double door wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and ...



We want to be your best choice for distribution box and cabinet. Our products are sold widely to more than 30 countries and regions. We accept customized and design together, if you have any special ...



NEXCONEC Lockable Double Door distribution box is supplied unloaded as standard and offers the ability to terminate up to 48 fibers housed in a strong metal enclosure for indoor application.



EASY TO OPERATE: The metal electrical enclosure box is equipped with a galvanized mounting back plate for easy installation of electrical components; the complete set of accessories and four ...




Ideal for use in power distribution panels, control systems, and general electrical installations, this double door enclosure is engineered to ensure safe and efficient operation of electrical equipment in ...



Equipped with two built-in slack spools and a lockable door, this box ensures safe ...




This distribution box controls and distributes power to lighting systems in commercial buildings and residential complexes. It can control the lighting levels, schedule, and other parameters.



Length:17.1mm
Small-end inner diameter:3.0mm
Large-end inner diameter:3.5mm
Outer diameter:5.5mm

Equipped with two built-in slack spools and a lockable door, this box ensures safe and organized routing of fiber in limited-space environments.



Length:19.8mm
Small-end inner diameter:3.0mm
Large-end inner diameter:3.3mm
Outer diameter:5.0mm

The box base is provided with cable outlets, and the door opens over 110 degrees with smooth rotation. It offers corrosion resistance, dust prevention, and rain protection.

Contact Us

For more information, pricing, or custom energy solutions, please contact us:

Website: <https://gdroofing.co.za>

Email: sales@gdroofing.co.za

Phone: +27 72 418 9365

Address: 22 Electron Avenue, Isando, Johannesburg, 1600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

